

ARCHITECTURAL

GRATES + DRAINS



65G90 **Linear Drain**

Developed for high capacity drainage needs, providing flexibility in landscape and pool design.

90mm Drainpipe with 65G UPVC Channel.

A 65mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 90mm drain below.

This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.

The Special Assembly is then completed with a stainless steel grate from the AR, TR or PS series.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.

Please note stainless steel grates to complement this system are separete items

SPECIFICATIONS + DIMENSIONS

Channel Width **Channel Depth** Length(s) **Outlet Size**

74mm 42mm 3000mm N/A

PRODUCT APPLICATIONS

Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage **Driveway Drainage** Pool and Spa Area Drainage

Paved Area Drainage Special Needs Drainage Suspended Slab Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 01/07/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au

42.0 diu able DN40 20.00 90mm

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions

74.2mm

Channel Material uPVC

